

General information on manufacturing possibilities

Flat foil Semi-tube (semi-sleeve) Tube (sleeve) Semi-tube cut through middle

Semi-tube with folds – right Semi-tube with folds cut through middle Tube with folds

- Flat foil
- Semi-tube (semi-sleeve)
- Tube (sleeve)
- Semi-sleeve cut through middle
- Semi-tube with folds – right
- Semi-tube with folds cut through middle
- Tube with folds

Manufacturing width of foils:

- w. 80 mm – 200 mm thickness 40 my to 120 my
- w. 220 mm – 450 mm thickness 30 my to 160 my
- w. 450 mm – 1000 mm thickness 30 my to 220 my
- w. 1000 mm – 1700 mm thickness 30 my to 220 my
- w. 1700 mm – 2600 mm thickness 30 my to 230 my
- palletizing tube with folds up to the perimeter of 6000 mm thickness from 30 my to 200 my

Manufacturing possibilities of ready-mades:

- Pouches and blanks from the width of 80 mm and pouch length 1200 mm with bottom and side weld
- Pouches and blanks and carrier bags with handhole, width from 120 mm to 750 mm with side weld
- Pouches and blanks, width from 120 mm to 1400 mm with bottom weld and fold
- Rolled pouches without cell, width from 200 mm to 1000 mm
- Bags with folds, width from 1000 mm to 1600 mm with bottom weld and fold, bulk or rolled on cell. Maximum length 10 bm.