

TECHNICAL SHEET

Technical data/ product composition	
object:	LD - PE – hose and half-hose
width:	60mm -1500 +/- 4%
side folds:	1000mm +/- 4%
circuit:	3000mm +/- 4%
length:	One roll approx... 1000m
power in my:	20-150 my +/- 5%
print:	-
UV stabilization:	6 months
Other specifications antiat	resistance 8 -10 ohm
density:	0,92 - 0,925 g/m3
transparency:	Standard, milky
Breaking strength:	longitudinal: 30N/mm2 / transverse: 28 N/mm2 (DIN 53455)
extension:	longitudinal: 550% / transverse: 540% (DIN 53456)
Basic properties:	The foil is suitable for making bags and for packing lines
Product quality:	The material properties and the quality of the foil are based on the technical sheets and commitments of our raw material suppliers.
warranty:	The foil quality warranty is 12 months from the date of manufacture (shown on the package), after the unpacking of the carton the warranty period is 6 months – according to UV stabilization
Logistic data/ product packaging	
Packing method:	Pallet rolls
Rolls on the pallet:	According to the instructions
Pallet size:	1200x800mm, EUR pallet tor EUR pallet size
Pallet wrapping:	Packed in protective foil, CAUTION: this package is not moisture proof
Product storage:	The roles must be stored in dry, covered areas in temperature range of -5°C to 30°C, it is necessary to leave the foil for at least 12 hours at operating temperature before using